

变更标记	日期	变更内容	签名	核准


P.0(XXX)	No. of Contact	A ±0.25	B ±0.13	C ±0.38	D ±0.13	E ±0.25
009	9	16.92	24.99	33.98	39.58	33.98
015	15	25.25	33.32	42.30	47.90	42.30
025	25	38.96	47.04	56.02	61.62	55.92
037	37	55.42	63.50	72.48	78.08	72.48

MATERIALS AND FINISH

SHELL : STEEL,TIN FINISHED
 INSULATOR : PBT UL94V-0 BLACK COLOR
 SIGNAL CONTACT: COPPER ALLOY,GOLD PLATED
 WATERTIGHT FRAME: PBT UL94-0 BLACK COLOR
 O-RING : SILICONE
 EPOXY SEALANT: EPOXY

ELECTRICAL CHARACTERISTICS

SIGNAL CONTACT CURRENT RATING: 5.0 AMPS
 SIGNAL CONTACT RESISTANCE: 15mΩ MAX
 DIELECTRIC WITHSTANDING VOLTAGE: 1000 V AC MIN.
 INSULATION RESISTANCE : 5GΩ MIN.
 TEMPERATURE RATING : -55°C ~ +105°C
 DEGREE OF PROTECTION: IP67 ACCORD

 **东莞扬顺五金电子有限公司**
 Dong Guan City Yang Shun Hardware Electron Co.,Ltd

未注公差		设计	刘峰	品名规格	DB XP 公头焊线式加防水圈	
X	±0.30	审核				
XX	±0.20	核准				
XXX	±0.10					
XXXX	±0.05					
X° ±2°	X.X' ±1°					