



PCB LAYOUT

DSI-X F X V X X X 7 0 0

Pin: 09 15 25 37
 COLOUR
 B:Blue K:Black W:White Z:661C
 Blue 3:235C Red 4:322C green
 6:131C Yellow

SHELL PLATING
 A:Gold B:Front Gold and back Tin C:Front Nickel and
 Back Tin N:Nickel T:Tin S:Zinc D:CU/ZNSN
 Contact Finish
 A:Gold Flash C:Gold Flash/3u" D:Gold Flash/5u" E:Gold Flash/10u"
 F:Gold Flash/30u" G:Gold T:Tin

变更标记	日期	变更内容	签名	核准
------	----	------	----	----

NOTICE :

- ELECTRICE:
 - DIELECTRIC RATING: 300V
 - CONTACT CURRENT RATING: 3AMP
 - CONTACT RESISTANCE: 15mΩ MAX.
 - INSULATION RESISTANCE: 1000MΩ MIN. at 500V DC
 - OPERATION TEMPERATURE: -55°C ~ 125°C
- MATERIAL:
 - INSULATOR: PBT+30% G.F (UL94V-0)
 - CONTACT: COPPER ALLOY
 - CONTACT PLATED: GOLD FLASH OVER NICKEL
 - SHELL: SPCC
 - SHELL PLATED: NICKEL/TIN
 - SCREW/FORK: COPPER ALLOY/PLATED NICKEL

P0(XXX)	A ±0.25	B ±0.13	C ±0.38	D ±0.25
009	16.33	24.99	30.81	19.15
015	24.66	33.32	39.14	27.51
025	36.38	47.04	53.04	41.28
037	54.84	63.50	69.32	57.71

东莞扬顺五金电子有限公司
 Dong Guan City Yang Shun Hardware Electron Co.,Ltd

未注公差	设计	刘峰	品名规格	D-SUB 180度高脚母 后脚20.2鱼叉螺母	
X. ±0.30	审核		料号	DS1-xF XVxxx700	型号
X.X ±0.20	核准		日期	2015.08.20	图号
X.XXX ±0.10	单位	mm	比例	1:1	版次
X.XXX ±0.05					A/0
X. ±2° X.X° ±1°					